

TOYOTA YARIS TECHNICAL SPECIFICATIONS

1.0-litre VVT-i petrol					
Code	1KR-FE				
Type	In-line 3-cylinder				
Valve mechanism	DOHC 12-valve with VVT-i				
Bore x stroke (mm)	71.0 x 84.0				
Displacement (cc)	998				
Compression ratio	11.5:1				
Max power (bhp/kW @ rpm)	68/51 @ 6,000				
Max torque (Nm @ rpm)	95 @ 4,300				
1.5-litre Dual VVT-iE petrol					
Code	2NR-FKE				
Type	In-line 4-cylinder				
Valve mechanism	16-valve DOHC with Dual VVT-iE				
Bore x stroke (mm)	72.5 x 90.6				
Displacement (cc)	1,496				
Compression ratio	13.5:1				
Max power (bhp/kW @ rpm)	110bhp/82kW @ 6,000				
Max torque (Nm @ rpm)	136 @ 4,400				
1.5-litre VVT-i Hybrid					
Code	1NZ-FXE				
Type	In-line 4-cylinder				
Valve mechanism	16-valve DOHC with VVT-i				
Bore x stroke (mm)	75 x 84.7				
Displacement (cc)	1,497				
Compression ratio	13.4:1				
Max power – full system (bhp/kW)	98/74				
Max engine power (bhp/kW @ rpm)	73/55 @ 4,800				
Max engine torque (Nm @ rpm)	111 @ 3,600 – 4,400				
Electric motor type	Permanent magnet, synchronous				
Max. output (bhp/kW)	59/45				
Max. torque (Nm)	169				
Battery type	Nickel-metal hydride				
TRANSMISSION		1.0 VVT-i	1.5-litre Dual VVT-iE		1.5 VVT-i Hybrid
		5MT	6MT	MDS	e-CVT
Gear ratios	1 st	3.545	3.538	-	-
	2 nd	1.913	1.913	-	-
	3 rd	1.310	1.392	-	-
	4 th	1.027	1.029	-	-
	5 th	0.850	0.818	-	-
	6 th	-	0.700	-	-
	Forward	-	-	2.480 – 0.396	-
	Reverse	3.214	3.333	2.604 – 1.680	-

Differential gear ratio		4.294	4.055	5.356	3.190
PERFORMANCE	1.0 VVT-i 5MT	1.5-litre Dual VVT-iE 6MT	1.5-litre Dual VVT-iE MDS	1.5 VVT-i Hybrid e-CVT	
0-62mph (sec)	15.3	11.0	11.2	11.8	
Maximum speed (mph)	96	109	109	103	
FUEL CONSUMPTION, EMISSIONS & INSURANCE	1.0 VVT-i 5MT	1.5-litre Dual VVT-iE 6MT	1.5-litre Dual VVT-iE MDS	1.5 VVT-i Hybrid e-CVT	
Combined (mpg, 15/16in wheel)	65.7	58.9/56.5	60.1/58.9	85.6/78.5	
Urban (mpg, 15/16in wheel)	54.3	45.6/44.9	47.9/47.0	91.1/85.6	
Extra Urban (mpg, 15/16in wheel)	74.3	70.6/67.3	70.6/68.9	85.6/78.5	
CO ₂ emissions 15in/16in wheel (g/km)	99	109/112	105/108	75/82	
Insurance groups	TBC				
Service schedule	10,000 miles/annually				
DIMENSIONS					
Overall length (mm)	3,945				
Overall width (mm)	1,695				
Overall height (mm)	1,510				
Wheelbase (mm)	2,510				
Track width – front (mm, 15in wheel/16in wheel)	1,485/1,465				
Track width – rear (mm)	1,470/1,455				
Overhang – front (mm)	810				
Overhang – rear (mm)	625				
Interior length (mm)	1,915				
Interior width (mm)	1,420				
Interior height (mm)	1,250				
VDA luggage capacity – rear seat up (l)	286				
Coefficient of drag (Cd)	0.29				
Fuel tank capacity (l)	42 36 (Hybrid)				
WEIGHTS	1.0 VVT-i	1.5 Dual VVT-iE		1.5 VVT-i Hybrid	
Kerb weight (kg)	980 – 1,040	1,040 – 1,125		1,090 – 1,165	
Gross vehicle weight (kg)	1,450	1,545		1,565	
SUSPENSION					
Front	MacPherson struts with anti-roll bar				
Rear	Torsion beam				
BRAKES	1.0 VVT-i	1.5 Dual VVT-iE		1.5 VVT-i Hybrid	
Front (mm)	258 ventilated discs	280 ventilated discs			

Rear (mm)	Drums/278 solid discs (Design & Hybrids)	278 solid discs
WHEELS & TYRES		
Wheel size	15in steel or alloy	16in alloy
Tyre size	175/65R15	195/50R16
STEERING		
Type	Rack and pinion, electric motor power assisted	
Ratio	12.8:1	
Turns – lock to lock (15in/16in wheels)	2.28/2.66	
Minimum turning circle – tyre/body (m)	9.6/10.0 (15in wheels) 10.2/11.0 (16in wheels)	

Ref: 170407M