

TOYOTA HILUX TECHNICAL SPECIFICATIONS

ENGINE		2.4-litre D-4D			
Engine code		2GD-FTV			
Type		4-cylinder in-line			
Valve mechanism		16-valve DOHC			
Displacement (cc)		2,393			
Bore x stroke (mm)		92.0 x 90.0			
Compression ratio		15.6:1			
Max. power (bhp/kW @ rpm)		148/110 @ 3,400			
Max. torque (Nm @ rpm)		400 @ 1,600 – 2,000			
TRANSMISSION		6MT	6AT		
Gear ratios	1 st	4.784	3.600		
	2 nd	2.423	2.090		
	3 rd	1.443	1.488		
	4 th	1.000	1.000		
	5 th	0.777	0.687		
	6 th	0.643	0.580		
	Reverse	4.066	3.732		
Differential gear ratio (final drive)		3.583	4.100		
BRAKES					
Front		Ventilated discs with fixed calliper, 4-cylinder			
Rear		Leading-trailing drums			
Additional features		ABS, BA, EBD, VSC, TSC, A-TRC, DAC, HAC			
SUSPENSION					
Front		Double wishbone			
Rear		Leaf springs, rigid axle			
STEERING					
Type		Rack and pinion			
Power steering		Hydraulic			
Min. turning radius (m)	Tyre	6.4			
	Body	6.7			
TYRES AND WHEELS					
Tyres		225/70R17 – Active S/Cab 265/65R17 – Active E/Cab, Active & Icon D/Cab 265/60R18 – Invincible & Invincible X			
Wheels		17 or 18in alloy			
PERFORMANCE		S/CAB	E/CAB	D/CAB	
Transmission		6MT	6MT	6MT	6AT
Max. speed (mph)		106	106	106	106
Acceleration 0-62mph (sec)		13.2	13.2	13.2	12.8
FUEL CONSUMPTION , EMISSIONS & INSURANCE		S/CAB	E/CAB	D/CAB	
Transmission		6MT	6MT	6MT	6AT
Fuel consumption – combined (mpg)		39.8	40.4	40.4	36.2

Fuel tank capacity (l)	80			
CO ₂ emissions – combined (g/km)	187	185	185	204
Insurance groups	41 - 50			
WEIGHTS	S/CAB	E/CAB	D/CAB	
Transmission	6MT	6MT	6MT	6AT
Kerb weight (kg)	1,800 – 1,850	1,915 – 1,965	2,100 – 2,160	2,095 – 2,155
Gross vehicle weight (kg)	n/a	3,150	3,210	3,210
TOWING CAPACITY				
Braked (kg)	3,500	3,500	3,200	3,200
Unbraked	750	750	750	750
EXTERIOR DIMENSIONS	S/CAB	E/CAB	D/CAB	
Overall length (mm)	5,330	5,330	5,330	
Overall width (mm)	1,800	1,855	1,855	
Overall height (mm)	1,795	1,810	1,815	
Wheelbase (mm)	3,085	3,085	3,085	
Front track (mm)	1,495	1,535	1,535	
Rear track (mm)	1,510	1,550	1,550	
Front overhang (mm)	1,000	1,000	1,000	
Rear overhang (mm)	,250	1,250	1,250	
Min. running ground clearance (mm)	277	289	293	
Angle of approach (deg)	30	31	31	
Angel of departure (deg)	25	26	26	
Drag coefficient (Cd, dependant on vehicle specification)	0.394	0.394	0.394	
INTERIOR DIMENSIONS	S/CAB	E/CAB	D/CAB	
Interior length (mm)	932	1,404	1,697	
Interior width (mm)	1,480	1,480	1,480 (front) 1,410 (rear)	
Interior height (mm)	1,175	1,170	1,170	
Couple distance (mm)	n/a	n/a	841	
Headroom (mm)	997	997 (front) 969 (rear)	997 (front) 969 (rear)	
DECK DIMENSIONS	S/CAB	E/CAB	D/CAB	
Length (mm)	2,315	1,810	1,525	
Max. width (mm)	1,645	1,645	1,645	
Height (mm)	480	480	480	

Ref:180122M