

TOYOTA RAV4 TECHNICAL SPECIFICATIONS

2.0-litre Valvematic	
Engine code	3ZR-FAE
Type	Four cylinders in-line
Valve mechanism	16-valve, DOHC, chain drive with Valvematic and Dual VVT-i
Fuel system	Electronic fuel injection
Bore x stroke (mm)	80.5 x 97.6
Displacement (cc)	1,987
Compression ratio	10.0:1
Max. power (bhp/kW @ rpm)	149/111 @ 6,200
Max. torque (Nm/rpm)	195 @ 4,400
2.5-litre VVT-i HYBRID - ENGINE	
Engine code	2AAR-FXE
Engine type	4 cylinders in-line
Valve mechanism	16-valve DOHC, VVT-i
Displacement (cc)	2,494
Bore x stroke (mm)	90.0 x 98.0
Compression ratio	12.5:1
Total system output – front electric motor and hybrid engine (bhp/kW)	195/145
Max. engine power (bhp/kW @ rpm)	150/112 @ 5,700
Max. engine torque (Nm @ rpm)	206 @ 4,400 – 4,800
2.5-litre VVT-i HYBRID – HYBRID SYSTEM	
Electric motor (front)	
Type	AC permanent magnet, synchronous motor
Max. power (bhp/kW)	141/105
Max. torque (Nm)	270
Electric motor (rear)	
Type	AC permanent magnet, synchronous motor
Max. power (bhp/kW)	68/50
Max. torque (Nm)	139
Hybrid battery	
Type	Nickel metal-hydride
Nominal voltage	244.8
Number of cells	204

System voltage		650		
Total system output – front electric motor and hybrid engine (bhp/kW)		195/145		
PERFORMANCE		2.0 Vmatic MDS AWD	2.5 HYBRID E-CVT FWD	2.5 HYBRID E-CVT AWD
Max. speed (mph)		115	112	112
0-62mph (sec)		9.9	8.4	8.4
FUEL CONSUMPTION, EMISSIONS & INSURANCE		2.0 Vmatic MDS AWD	2.5 HYBRID E-CVT FWD	2.5 HYBRID E-CVT AWD
Combined (mpg)	17in wheel	-	57.6	-
	18in wheel	43.5	-	55.4
Urban (mpg)	17in wheel	-	57.6	-
	18in wheel	34.4	-	55.4
Extra-urban (mpg)	17in wheel	-	56.5	-
	18in wheel	50.4	-	57.6
Fuel tank capacity (l)		60	56	
CO ₂ (g/km, combined)	17in wheel	-	115	-
	18in wheel	152	-	118
Insurance groups		22E/23E	27E	28E/29A
SUSPENSION				
Front		MacPherson strut		
Rear		Double wishbone		
BRAKES				
Front (diameter x thickness, mm)		Ventilated discs 296 x 28		
Rear (diameter x thickness, mm)		Solid discs 281 x 12		
Additional features		ABS, Electronic Brakeforce Distribution, Brake Assist, Downhill Assist Control (A/T models only). Hill-start Assist Control, VSC, Traction Control		
STEERING				
Type		Rack and pinion, Electric Power Steering		
Ratio		14.5:1		
Turns lock to lock		2.83		

Min. Turning circle – tyre/body (m)	5.3/5.7 – 17in wheel 5.6/6.0 – 18in wheel		
TYRES AND WHEELS			
Wheel size	17 x 7J alloy		18 x 7.5J alloy
Tyre size	225/65R17		235/55R18
WEIGHTS	2.0 Vmatic AWD MDS	2.5 HYBRID E-CVT FWD	2.5 HYBRID E-CVT AWD
Kerb weight (min/max kg)	1,605 – 1,615	1,710	1,775 – 1,810
Towing capacity - unbraked (kg)	750	750	750
Towing capacity - braked (kg)	1,500	800	1,650
Gross Vehicle Weight (kg)	2,110	2,205	2,205
TRANSMISSION	2.0 Vmatic AWD MDS	2.5 HYBRID E-CVT FWD	2.5 HYBRID E-CVT AWD
GEAR RATIOS			
Reverse	1.751	-	-
Final gear ratio	1 st – 4 th	2.277	-
	5 th , 6 th	5.791	-
	Differential	-	3.750
DIMENSIONS – EXTERIOR			
Overall length (mm)	4,605		
Overall width (mm)	1,845		
Overall height (mm)	1,675		
Wheelbase (mm)	2,660		
Front track (mm)	1,570 – 17in wheel 1,560 – 18in wheel		
Rear track (mm)	1,570 – 17in wheel 1,560 – 18in wheel		
Front overhang (mm)	930		
Rear overhang (mm)	1,015		
Coefficient of drag (Cd)	0.34 – 0.36		
DIMENSIONS – INTERIOR			
Interior length (mm)	1,935		
Interior width (mm)	1,505		

Interior height (mm)	1,220
DIMENSIONS – LUGGAGE COMPARTMENT	
Capacity – seats in place (l)	547 501 - Hybrid
Capacity – seats folded, up to roof (l)	1,735 1,633 - Hybrid
Load area length (mm)	1,025
Load area width (mm)	1,335
Load area height (mm)	945

Ref: 180122M