

LAND CRUISER UTILITY COMMERCIAL TECHNICAL SPECIFICATIONS

ENGINE		2.8 D-4D	
Engine type		Four cylinders in-line	
Displacement (cc)		2,755	
Valvetrain		16-valve DOHC	
Fuel injection type		Common rail	
Emissions level		Euro 6	
Bore x stroke (mm)		92 x 103.6	
Compression ratio		15.6:1	
Max power (bhp/kW @ rpm)		174/130 @ 3,400	
Max torque (Nm/rpm)		420 @ 1,400 – 2,600	
TRANSMISSION			
Type		6MT	
Ratios	1 st	4.171	
	2 nd	2.190	
	3 rd	1.488	
	4 th	1.193	
	5 th	1.000	
	6 th	0.799	
	Reverse	3.607	
PERFORMANCE			
Acceleration 0-62mph (sec)		12.1	
Max. speed (mph)		108	
FUEL CONSUMPTION AND EMISSIONS			
Combined (mpg)		37.6	
Urban (mpg)		31.7	
Extra urban (mpg)		42.1	
CO ₂ emissions (g/km)		197	
Fuel tank capacity (l)		87	
Insurance groups		43E	44E
SUSPENSION			
Front		Double wishbone	
Rear		Four-link with lateral rod	
BRAKES			
Front		Ventilated discs	
Rear		Ventilated discs	
TYRES AND WHEELS			
Wheels		17in	
Tyres		245/70R17	
OFF-ROAD PERFORMANCE			
Approach angle (°)		31	
Departure angle (°)	3-door	26	
	5-door	25	
Ramp angle (°)	3-door	22	
	5-door	22	
Side angle limit (°)		42	
Climbing angle limit (°)		42	

Minimum running ground clearance (mm)	3-door	205
	5-door	215
Wading depth (mm)		700
DIMENSIONS		
Overall length (mm)	3-door	4,395
	5-door	4,840
Overall width (mm)		1,885
Overall height (mm)	3-door	1,830
	5-door	1,845
Wheelbase (mm)	3-door	2,450
	5-door	2,790
Front overhang (mm)		975
Rear overhang (mm)	3-door	970
	5-door	1,075
Front track (mm)		1,585
Rear track (mm)		1,585
Turning radius – tyre (m)	3-door	5.2
	5-door	5.8
Load area capacity, all seats up, loaded to roof (l)	3dr	1,574
	5dr	2,216
WEIGHTS		
Kerb weight (kg)	3-door	1,975
	5-door	2,225
Payload (kg)	3dr	488 – 593
	5dr	661 - 756
Gross vehicle weight (kg)	3-door	2,600
	5-door	2,930
Towing capacity – braked (kg)		3,000
Towing capacity – unbraked (kg)		750

180614M