

TOYOTA PROACE VAN TECHNICAL SPECIFICATIONS

POWERTRAIN				
	1.5 diesel 100		1.5 diesel 120	
Type	Four cylinders in-line			
Capacity (cc)	1,499			
Bore x stroke (mm)	75.0 x 84.8			
Compression ratio	16.5:1			
Fuel injection system	Common rail diesel direct injection			
Max. power (bhp/DIN hp/kW @ rpm)	101/102/75 @ 3,500		118/120/88 @ 3,500	
Max. torque (Nm @ rpm)	270 @ 2,000		300 @ 2,000	
	2.0 diesel 120		2.0 diesel 180	
Type	Four cylinders in-line			
Capacity (cc)	1,997			
Bore x stroke (mm)	85.0 x 88.0			
Compression ratio	16.7:1			
Fuel injection system	Common rail diesel direct injection			
Max. power (bhp/DIN hp/Kw @ rpm)	121/122/90 @ 3,750		174/177/130 @ 3,750	
Max. torque (Nm @ rpm)	340 @ 2,000		400 @ 2,000	
PERFORMANCE	1.5D 100	1.5D 120	2.0D 120	2.0D 180
Max. speed (mph)	90	99	105	105
0-62mph (sec)	tbc	12.0	13.3	8.5
FUEL CONSUMPTION (mpg, WLTP)	1.5D 100	1.5D 120	2.0D 120	2.0D 180
Active Compact	TBC	-	-	-
Icon Compact	TBC	-	-	-
Active Medium	TBC	TBC	TBC	-
Icon Medium	-	TBC	TBC 7	-
Combi Medium	-	TBC	-	-
Icon Crew Cab	-	-	TBC	-
Design Medium	-	-	TBC	TBC
Design Crew Cab	-	-	TBC	TBC
Active Long	-	-	TBC	-
Active Long	-	-	TBC	-
Fuel tank capacity (l)	69			
Insurance groups	37E – 46E			
CO₂ EMISSIONS (WLTP, g/km)	1.5D 100	1.5D 120	2.0D 120	2.0D 180

Active Compact		TBC	-	-	-	
Icon Compact		TBC	-	-	-	
Active Medium		TBC	TBC	TBC	-	
Icon Medium		-	TBC	TBC	-	
Combi Medium		-	TBC	-	-	
Icon Crew Cab		-	-	TBC	-	
Design Medium		-	-	TBC	TBC	
Design Crew Cab		-	-	TBC	TBC	
Active Long		-	-	TBC	-	
Active Long		-	-	TBC	-	
TRANSMISSION		1.5D 100	1.5D 120	2.0D 120	2.0D 180	
Type		6MT	6MT	6MT	8AT	
Gear ratios (km/h per 1,000rpm)	1 st	7.47	7.54	7.54	7.70	
	2 nd	14.27	14.39	14.39	13.30	
	3 rd	23.34	23.54	23.54	20.70	
	4 th	33.113	33.42	33.42	28.50	
	5 th	41.37	41.73	41.73	34.40	
	6 th	50.33	50.76	50.76	42.50	
	7 th	-	-	-	53.00	
	8 th	-	-	-	63.10	
BRAKES						
Front		Ventilated discs				
Rear		Solid discs				
STEERING		Compact	Medium	Long		
Type		Electro-hydraulic, rack and pinion				
Turning circle (m)	Tyre	11.3	12.4	12.4		
	Body	11.8	12.9	12.9		
SUSPENSION						
Front		MacPherson-type with anti-roll bar, variable stiffness springs and load-adaptive shock absorbers				
Rear		Wishbones with trailing arms, variable stiffness springs and load-adaptive shock absorbers				
EXTERIOR DIMENSIONS		COMPACT	MEDIUM	CREW CAB MEDIUM	CREW CAB LONG	LONG
Overall length (mm)		4,609	4,959	4,959	5,309	5,309
Overall width – excluding door mirrors (mm)		1,920	1,920	1,920	1,920	1,920
Overall width – including door mirrors (mm)		2,204	2,204	2,204	2,204	2,204

Overall height (mm)	1,910	1,899 1,940*	1,899* 1,940*	1,940	1,940
Wheelbase (mm)	2,925	3,275	3,275	3,275	3,275
Front track (mm)	1,630	1,630	1,630	1,630	1,630
Rear track (mm)	1,618	1,618	1,618	1,618	1,618
Front overhang (mm)	881	881	881	881	881
Rear overhang (mm)	803	803	803	1,153	1,153
LOAD AREA DIMENSIONS	COMPACT	MEDIUM	CREW CAB MEDIUM	CREW CAB LONG	LONG
Floor load length (mm)	2,162	2,512	1,488**	1,838**	2,862
Floor load length with Smart Cargo (mm)	3,324	3,674	n/a	n/a	4,026
Mid-height load length (mm)	1,835	2,185	1,700	Tbc	2,535
Max. load height (mm)	1,397	1,397	1,337	1,339	1,397
Max. load width between sides (mm)	1,636	1,636	1,618	1,618	1,636
Max. load width between wheel arches (mm)	1,258	1,258	1,258	1,258	1,258
Sliding side door max. opening height (mm)	1,238	1,258	1,258	1,258	1,258
Sliding side door max. opening width (mm)	1,282	1,282	1,282	1,282	1,282
Load area volume (m ³)	4.6	5.3	3.2	4.0	6.1
Load area volume with Smart Cargo (m ³)	5.1	5.8	n/a	n/a	6.6
WEIGHTS		1.5D 100 6MT	1.5D 120 6MT	2.0D 120 6MT	2.0D 180 8AT
Gross train weight (kg)	Compact	4,020	n/a	n/a	n/a
	Medium	4,035	4,040	5,000	4,900
	Medium Combi	n/a	4,155	n/a	n/a
	Medium Crew Cab	n/a	n/a	5,000	4,900
	Long	n/a	n/a	5,000	n/a
	Long Crew Cab	n/a	n/a	5,000	4,900
Gross vehicle weight (kg)	Compact	2,620	n/a	n/a	n/a
	Medium	2,635	2,660	3,100	2,760

	Medium Combi	n/a	2,755	n/a	n/a
	Medium Crew Cab	n/a	n/a	3,060	2,830
	Long	n/a	n/a	3,100	n/a
	Long Crew Cab	n/a	n/a	2,940	3,000
Kerb weight (kg)	Compact	1,660	n/a	n/a	n/a
	Medium	1,660	1,581	1,642	1,681
	Medium Combi	n/a	1,660	n/a	n/a
	Medium Crew Cab	n/a	n/a	1,769	1,770
	Long	n/a	n/a	1,685	n/a
	Long Crew Cab	n/a	n/a	1,770	1,816
Max, towing capacity – braked (kg)	Compact	1,400	n/a	n/a	n/a
	Medium	1,400	1,800	2,500	2,300
	Medium Combi	n/a	1,800	n/a	n/a
	Medium Crew Cab	n/a	n/a	2,500	2,070
	Long	n/a	n/a	2,500	n/a
	Long Crew Cab	n/a	n/a	2,500	2000
Max, towing capacity – unbraked (kg)	Compact	750	n/a	n/a	n/a
	Medium	750	750	750	750
	Medium Combi	n/a	750	n/a	n/a
	Medium Crew Cab	n/a	n/a	750	750
	Long	n/a	n/a	750	n/a
	Long	n/a	n/a	750	750

	Crew Cab				
WHEELS & TYRES					
Wheel type and size	16 or 17in steel OR 17in alloy				
Tyre size	215/65R16 or 215/60R17				

EXTERIOR DIMENSIONS	COMPACT	MEDIUM	CREW CAB MEDIUM	CREW CAB LONG	LONG
Overall length (mm)	4,609	4,959	4,959	5,309	5,309
Overall width – excluding door mirrors (mm)	1,920	1,920	1,920	1,920	1,920
Overall width – including door mirrors (mm)	2,204	2,204	2,204	2,204	2,204
Overall height (mm)	1,910	1,899 1,940*	1,899* 1,940*	1,940	1,940
Wheelbase (mm)	2,925	3,275	3,275	3,275	3,275
Front track (mm)	1,630	1,630	1,630	1,630	1,630
Rear track (mm)	1,618	1,618	1,618	1,618	1,618
Front overhang (mm)	881	881	881	881	881
Rear overhang (mm)	803	803	803	1,153	1,153
LOAD AREA DIMENSIONS	COMPACT	MEDIUM	CREW CAB MEDIUM	CREW CAB LONG	LONG
Floor load length (mm)	2,162	2,512	1,488**	1,838**	2,862
Floor load length with Smart Cargo (mm)	3,324	3,674	n/a	n/a	4,026
Mid-height load length (mm)	1,835	2,185	1,700	Tbc	2,535
Max. load height (mm)	1,397	1,397	1,337	1,339	1,397
Max. load width between sides (mm)	1,636	1,636	1,618	1,618	1,636
Max. load width between wheel arches (mm)	1,258	1,258	1,258	1,258	1,258
Sliding side door max. opening height (mm)	1,238	1,258	1,258	1,258	1,258
Sliding side door max. opening width (mm)	1,282	1,282	1,282	1,282	1,282
Load area volume (m ³)	4.6	5.3	3.2	4.0	6.1
Load area volume with Smart Cargo (m ³)	5.1	5.8	n/a	n/a	6.6
WEIGHTS	1.5D 100 6MT	1.5D 120 6MT	2.0D 120 6MT	2.0D 180 8AT	

Gross train weight (kg)	Compact	4,020	n/a	n/a	n/a
	Medium	4,035	4,040	5,000	4,900
	Medium Combi	n/a	4,155	n/a	n/a
	Medium Crew Cab	n/a	n/a	5,000	4,900
	Long	n/a	n/a	5,000	n/a
	Long Crew Cab	n/a	n/a	5,000	4,900
	Gross vehicle weight (kg)	Compact	2,620	n/a	n/a
Medium		2,635	2,660	3,100	2,760
Medium Combi		n/a	2,755	n/a	n/a
Medium Crew Cab		n/a	n/a	3,060	2,830
Long		n/a	n/a	3,100	n/a
Long Crew Cab		n/a	n/a	2,940	3,000
Kerb weight (kg)		Compact	1,660	n/a	n/a
	Medium	1,660	1,581	1,642	1,681
	Medium Combi	n/a	1,660	n/a	n/a
	Medium Crew Cab	n/a	n/a	1,769	1,770
	Long	n/a	n/a	1,685	n/a
	Long Crew Cab	n/a	n/a	1,770	1,816
	Max, towing capacity – braked (kg)	Compact	1,400	n/a	n/a
Medium		1,400	1,800	2,500	2,300
Medium Combi		n/a	1,800	n/a	n/a
Medium Crew Cab		n/a	n/a	2,500	2,070
Long		n/a	n/a	2,500	n/a

	Long Crew Cab	n/a	n/a	2,500	2000
Max, towing capacity – unbraked (kg)	Compact	750	n/a	n/a	n/a
	Medium	750	750	750	750
	Medium Combi	n/a	750	n/a	n/a
	Medium Crew Cab	n/a	n/a	750	750
	Long	n/a	n/a	750	n/a
	Long Crew Cab	n/a	n/a	750	750

ENDS

Ref:200812M