RAV4 TECHNICAL SPECIFICATIONS

2.5-litre HYBRID ENGII	NE			
Engine code		A25A	A25A-FXS	
Engine type		4 cylinders in-line		
Valve mechanism		16-valve DOHC, VVT-i (intake) and VVT-i (exhaust)		
Fuel injection		D4S		
Displacement (cc)		2,487		
Bore x stroke (mm)		87.5 x 103.48		
Compression ratio		14.0:1		
Total system output (bhp/kW)		215/160 FWD 219/163 AWD-i		
Max. engine power (bhp/kW @ rpm)		176/131 @ 5,700		
Max. engine torque (Nm @ rpm)			221 @ 3,600 – 5,200	
Emissions certification		Euro 6d		
HYBRID SYSTEM				
Electric motor (front)				
Туре		AC permanent magnet, synchronous motor		
Max. power (kW)			88	
Max. torque (Nm)		20	202	
Electric motor (rear)		AC name an act was a wart as a		
Type		AC permanent magnet, synchronous motor		
Max. power (kW) Max. torque (Nm)		40 121		
Hybrid battery		121		
Type		Nickel-metal hydride		
Nominal voltage		244.8		
Number of modules		34		
System voltage		650		
TRANSMISSION				
Туре		CVT		
Final drive ratio		3.605:1		
PERFORMANCE		FWD	AWD-i	
Max. speed (mph)		11	2	
0-62mph (sec)	0-62mph (sec)		8.1	
FUEL CONSUMPTION, EMISSIONS & INSURANCE		FWD	AWD-i	
Combined fuel	Icon	48.8-50.4	n/a	
consumption – WLTP data (mpg)	Design	48.8-49.6	47.9-48.7	
	Excel	47.9-48.7	47.9-47.9	
	Dynamic	47.9-48.7	47.9-47.9	
Fuel tank capacity (I)			55	
CO ₂ emissions – combined, WLTP data (g/km)	Icon	126-131	n/a	
	Design	129-131	131-134	
	Excel	131-133	133-136	
	Dynamic	131-133		
Insurance groups		25E-30A		
New vehicle warranty		5 years/100	5 years/100,000 miles	

SUSPENSION			
Front		MacPherson strut	
Rear		Double wishbone	
Anti-roll bar diameter	Front	25.4	
(mm)	Rear	23.2	
BRAKES			
Front (diameter, mm)		Ventilated discs, 328	
Rear (diameter, mm)		Solid discs, 317	
STEERING			
Туре		Rack and pinion, electric power steering	
Ratio		14.3:1	
Turns lock to lock		2.76	
Min. turning radius – tyre/body (m)		5.5/5.9	
TYRES AND WHEELS			
Wheel size		17, 18 or 19-inch	
Tyre size		225/65R17	
		225/60R18	
		235/55R19	
WEIGHTS		FWD	AWD-i
Kerb weight (min/max k	<u> </u>	1,590 – 1,680	1,650 – 1,730
Towing capacity - unbraked (kg)		75	0
Towing capacity - braked (kg)		800	1,650
Gross Vehicle Weight (kg	9,	2,135	2,225
DIMENSIONS - EXTER	IOR		
Overall length (mm)		4,600	
Overall width (mm)		1,855	
Overall height (mm)		1,685	
Wheelbase (mm)		2,690	
Front track (mm)		1,610	
Rear track (mm)		1,640	
Front overhang (mm)		910	
Rear overhang (mm)		1,000	
Ground clearance (mm)		195	
Angle of approach (deg)		17.5	
Angle of departure (deg)		20	
Coefficient of drag (Cd)		0.32	
DIMENSIONS - INTERIO	OR		
Interior length (mm)		1,890	
Interior width (mm)		1,515	
Interior height (mm)		1,230	
DIMENSIONS - LUGGA			
Capacity – rear seats in place (I)		580	
Capacity – rear seats folded, up to tonneau cover		1,189	
(1)			
Capacity – rear seats folded, up to roof (I)		1,690	
Load area height (mm)		1,015	