

TOYOTA PROACE CITY TECHNICAL SPECIFICATIONS

ENGINE		1.5 100	1.5 130
Type		4 cylinders, in-line	
Capacity (cc)		1,499	
Bore x stroke (mm)		75 x 84.8	
Compression ratio		16.5:1	
Fuel injection system		Common rail, direct injection	
Max. power (bhp/DIN hp/kW @ rpm)		101/102/75 @ 3,500	x/x/96 @ 3,7550
Max. torque (Nm @ rpm)		250 @ 1,750	300 @ 1,750
TRANSMISSION			
Transmission type		6-speed manual	
Gear ratios	1 st	0.289	0.268
	2 nd	0.488	0.512
	3 rd	0.775	0.837
	4 th	1.108	1.189
	5 th	1.468	1.484
	6 th	1.862	1.806
	Reverse	3.333	
Differential gear ratio		0.239	0.258
PERFORMANCE			
Max. speed (mph)		102	115
0-62mph acceleration (sec)		11.5	9.8
FUEL CONSUMPTION, EMISSIONS, SERVICING. INSURANCE		1.5 100	1.5 130
Combined cycle fuel consumption WLTP, mpg)	Active	47.55-51.36	-
	Icon	47.55-51.36 SWB 42.9-51.36 LWB	-
	Design	-	47.12-50.44
Combined cycle CO ₂ emissions (WLTP, g/km)	Active	144-155.7	-
	Icon	144-155.65 SWB 145-171.37 LWB	-
	Design	-	146-157.08
Service intervals		25,000 miles/2 years	
Insurance groups		32E – 34E	
Fuel tank capacity (l)		50 + 17 for AdBlue	

BRAKES		
Front	Ventilated discs	
Rear	Discs	
STEERING		
Type	Speed-sensitive electric power-assisted	
Turning circle – tyre (m)	10.79	11.43
Turning circle – body (m)	11.29	11.93
SUSPENSION		
Front	MacPherson struts, anti-roll bar	
Rear	Torsion beam	
EXTERIOR DIMENSIONS		
Overall length (mm)	4,403	4,753
Overall width – exc. mirrors (mm)	1,848	
Overall width – mirrors folded (mm)	2,107	
Overall height (mm)	1,880	
Wheelbase (mm)	2,785	2,975
Front track (mm)	1,548	
Rear track (mm)	1,568	
Front overhang (mm)	892	
Rear overhang (mm)	726	
Ground clearance (mm)	160	
LOAD COMPARTMENT (INTERIOR) DIMENSIONS		
Load floor length (mm)	1,817	2,167
Load floor length with Smart Cargo (mm)	3,090	3,440
Max. load height (mm)	1,200	
Max. load width – between sides (mm)	1,527	
Max. load width – between wheel arches (mm)	1,229	
Sliding side door max. opening height (mm)	1,072	
Sliding side door max. opening width (mm)	675	
Rear doors max. opening height (mm)	1,196	
Rear doors max. opening width – upper section (mm)	1,087	

Rear doors max. opening width – lower section (mm)	1,241		
Load area volume (m ³)	3.3	3.9	
Load area volume with Smart Cargo (m ³)	3.8	4.4	
WEIGHTS	Active	Icon	Design
Gross vehicle weight (kg)	2,390	2,390 2,400*	2,380
Min. kerb weight (kg)	1,404	1,404 1,426*	1,404
Max. kerb weight (kg)	1,627	1,702 1,693*	1,627
Towing capacity – unbraked (kg)	720	730 740*	730
Towing capacity – braked (kg)	1,200	1,200	1,200
Payload (kg)	1,000	1,000	1,000

* Values for long wheelbase model