

TOYOTA PROACE VAN TECHNICAL SPECIFICATIONS

POWERTRAIN				
	1.5 diesel 100		1.5 diesel 120	
Type	Four cylinders in-line			
Capacity (cc)	1,499			
Bore x stroke (mm)	75.0 x 84.8			
Compression ratio	16.5:1			
Fuel injection system	Common rail diesel direct injection			
Max. power (bhp/DIN hp/kW @ rpm)	101/102/75 @ 3,500		118/120/88 @ 3,500	
Max. torque (Nm @ rpm)	270 @ 2,000		300 @ 2,000	
	2.0 diesel 140		2.0 diesel 180	
Type	Four cylinders in-line			
Capacity (cc)	1,997			
Bore x stroke (mm)	85.0 x 88.0			
Compression ratio	16.7:1			
Fuel injection system	Common rail diesel direct injection			
Max. power (bhp/DIN hp/kW @ rpm)	142/144/106 @ 3,750		174/177/130 @ 3,750	
Max. torque (Nm @ rpm)	340 @ 2,000		400 @ 2,000	
PERFORMANCE	1.5D 100	1.5D 120	2.0D 140	2.0D 180
Max. speed (mph)	90	99	105	105
0-62mph (sec)	tbc	12.0	12.5	8.5
FUEL CONSUMPTION (mpg, WLTP)	1.5D 100	1.5D 120	2.0D 140	2.0D 180
Active Compact	39.19 – 42.8	-	-	-
Active Medium	39.19 – 42.16	39.19 – 42.16	-	-
Active Long	-	-	35.7 – 37.66	-
Icon Compact	39.19 – 42.16	-	-	-
Icon Medium	-	39.19 – 42.16	37.0 – 38.17	-
Icon Long	-	-	35.7 -38.17	-
Design Medium	-	-	35.7 – 38.17	35.7 – 38.7
Icon Crew Cab Medium	-	-	35.7 – 37.66	-
Icon Crew Cab Long	-	-	35.7 – 37.66	-
Design Crew Cab Medium	-	-	35.7 – 37.66	35.7 – 38.17
Design Crew Cab Long	-	-	35.7 – 37.17	35.7 – 36.69
Combi	-	40.87 – 44.14	-	-
Fuel tank capacity (l)	69			
Insurance groups	37E – 46E			

CO₂ EMISSIONS (WLTP, g/km)		1.5D 100	1.5D 120	2.0D 140	2.0D 180	
Active Compact		174	-	-	-	
Active Medium		175	175	-	-	
Active Long		-	-	195	-	
Icon Compact		174	-	-	-	
Icon Medium		-	175	194	-	
Icon Long		-	-	196	-	
Design Medium		-	-	195	192	
Icon Crew Cab Medium		-	-	196	-	
Icon Crew Cab Long		-	-	197	-	
Design Crew Cab Medium		-	-	197	194	
Design Crew Cab Long		-	-	198	201	
Combi		-	169	-	-	
TRANSMISSION		1.5D 100	1.5D 120	2.0D 140	2.0D 180	
Type		6MT	6MT	6MT	8AT	
BRAKES						
Front		Ventilated discs				
Rear		Solid discs				
STEERING		Compact	Medium	Long		
Type		Electro-hydraulic, rack and pinion				
Turning circle (m)	Tyre	11.3	12.4	12.4		
	Body	11.8	12.9	12.9		
SUSPENSION						
Front		MacPherson-type with anti-roll bar, variable stiffness springs and load-adaptive shock absorbers				
Rear		Wishbones with trailing arms, variable stiffness springs and load-adaptive shock absorbers				
EXTERIOR DIMENSIONS		COMPACT	MEDIUM	CREW CAB MEDIUM	CREW CAB LONG	LONG
Overall length (mm)		4,609	4,959	4,959	5,309	5,309
Overall width – excluding door mirrors (mm)		1,920	1,920	1,920	1,920	1,920
Overall width – including door mirrors (mm)		2,204	2,204	2,204	2,204	2,204
Overall height (mm)		1,910	1,899 1,940	1,899 1,940	1,940	1,940
Wheelbase (mm)		2,925	3,275	3,275	3,275	3,275
Front track (mm)		1,630	1,630	1,630	1,630	1,630

Rear track (mm)		1,618	1,618	1,618	1,618	1,618
Front overhang (mm)		881	881	881	881	881
Rear overhang (mm)		803	803	803	1,153	1,153
LOAD AREA DIMENSIONS		COMPACT	MEDIUM	CREW CAB MEDIUM	CREW CAB LONG	LONG
Floor load length (mm)		2,162	2,512	1,488	1,838	2,862
Floor load length with Smart Cargo (mm)		3,324	3,674	n/a	n/a	4,026
Mid-height load length (mm)		1,835	2,185	1,700	Tbc	2,535
Max. load height (mm)		1,397	1,397	1,337	1,339	1,397
Max. load width between sides (mm)		1,636	1,636	1,618	1,618	1,636
Max. load width between wheel arches (mm)		1,258	1,258	1,258	1,258	1,258
Sliding side door max. opening height (mm)		1,238	1,258	1,258	1,258	1,258
Sliding side door max. opening width (mm)		1,282	1,282	1,282	1,282	1,282
Load area volume (m ³)		4.6	5.3	3.2	4.0	6.1
Load area volume with Smart Cargo (m ³)		5.1	5.8	n/a	n/a	6.6
WEIGHTS		1.5D 100 6MT	1.5D 120 6MT	2.0D 140 6MT	2.0D 180 8AT	
Gross vehicle weight (kg)	Compact	2,620	n/a	n/a	n/a	
	Medium	2,635	2,660	3,100	2,760	
	Medium Combi	n/a	2,755	n/a	n/a	
	Medium Crew Cab	n/a	n/a	3,030	2,830	
	Long	n/a	n/a	3,100	n/a	
	Long Crew Cab	n/a	n/a	3,030	3,000	
	Min. kerb weight (kg)	Compact	1,660	n/a	n/a	n/a
	Medium	1,660	1,581	1,654	1,681	
	Medium Combi	n/a	1,660	n/a	n/a	

	Medium Crew Cab	n/a	n/a	1,770	1,770
	Long	n/a	n/a	1,692	n/a
	Long Crew Cab	n/a	n/a	1,770	1,816
Max, towing capacity – braked (kg)	Compact	1,400	n/a	n/a	n/a
	Medium	1,400	1,800	2,500	2,300
	Medium Combi	n/a	1,800	n/a	n/a
	Medium Crew Cab	n/a	n/a	2,500	2,070
	Long	n/a	n/a	2,500	n/a
	Long Crew Cab	n/a	n/a	2,500	2000
Max, towing capacity – unbraked (kg)	Compact	750	n/a	n/a	n/a
	Medium	750	750	750	750
	Medium Combi	n/a	750	n/a	n/a
	Medium Crew Cab	n/a	n/a	750	750
	Long	n/a	n/a	750	n/a
	Long Crew Cab	n/a	n/a	750	750
WHEELS & TYRES					
Wheel type and size		16 or 17in steel or 17in alloy			
Tyre size		215/65R16 or 215/60R17			