

TOYOTA bZ4X TECHNICAL SPECIFICATIONS

DRIVETRAIN		FWD	X-MODE AWD
Electric motors			
Type		AC permanent magnet, synchronous motor	
Total power (bhp/DIN hp/kW)		201/204/150	215/218/160
Front motor max. power (bhp/DIN hp/kW)		201/204/150	107/109/80
Rear motor max. power (bhp/DIN hp/kW)		-	107/109/90
Max. torque (Nm)		266	337
Battery			
Type		Lithium-ion	
Nominal voltage		355	
Capacity (kWh)		71.4	
Number of cells		96	
PERFORMANCE		FWD	X-MODE AWD
0-62mph (sec)*		7.5	6.9
Max. speed (mph)*		100	
Driving range (miles, WLTP)	Pure	317	-
	Motion	312	286
	Vision	277	259
	Premiere Edition	-	257
Electric energy consumption (combined, miles/kWh)		4.4	4.0
DIMENSIONS		FWD	X-MODE AWD
Overall length (mm)		4,690	
Overall width – excluding mirrors (mm)		1,860	
Overall height (mm)		1,600	
Wheelbase (mm)		2,640	
Track front (mm)		1,600	
Track rear (mm)		1,610	
Front overhang (mm)		915	
Rear overhang (mm)		925	
INTERIOR DIMENSIONS		FWD	X-MODE AWD
Interior length (mm)		1,940	
Interior width (mm)		1,515	
Interior height (mm)		1,109 1,160 (1,146 with Skyview roof)	
Load capacity (inc. under deckboard, VDA litres)		452	
WEIGHTS		FWD	X-MODE AWD
Kerb weight (kg)		1,910-1,970	2,000-2,060
Gross vehicle weight (kg)		2,465	2,550
Towing capacity (kg)		750	
INSURANCE, SERVICING & WARRANTY			

Insurance group		TBC	
Service intervals		10,000 miles/annually	
Comprehensive new vehicle warranty		3 years/60,000 miles	
Battery warranty		8 years/100,000 miles 10 years/600,000 miles with EV Care Battery Health Check	
Corrosion/perforation warranty		12 years/unlimited mileage	
Surface rust/paintwork		3 years/unlimited mileage	
SUSPENSION			
Front		MacPherson strut	
Rear		Trailing arms	
BRAKES			
Front		Ventilated discs	
Rear		Ventilated discs	
Parking brake		Electronic	
STEERING			
Type		Rack and pinion, electric power steering	
Turns (lock to lock)		2.81	
Min. turning radius (m)	Tyre	5.6	
	Body	6.1	
WHEELS & TYRES			
Wheel and tyre size		18in, 235/60R18 20in, 235/50R20	
OFF-ROAD PERFORMANCE			
Angle of approach (deg)		17.4	
Angle of departure (deg)		25.6	
Min. running ground clearance (mm)		177 (with one passenger)	
Wading depth (mm)		500	