## **TOYOTA PROACE CITY TECHNICAL SPECIFICATIONS**

ENGINE		1.5 100	1.5 130		
Туре		4 cylinder	4 cylinders, in-line		
Capacity (cc)		1,499			
Bore x stroke (mm)		75 x 84.8			
Compression ratio		16.5:1			
Fuel injection system		Common rail, o	Common rail, direct injection		
Max. power (bhp/DIN hp/kW @ rpm)		101/102/75 @ 3,500	x/x/96 @ 3,7550		
Max. torque (Nm @ rpm)		250 @ 1,750	300 @ 1,750		
TRANSMISSION					
Transmission type		6-speed	6-speed manual		
Gear ratios	1 <sup>st</sup>	0.289	0.268		
	2 <sup>nd</sup>	0.488	0.512		
	3 <sup>rd</sup>	0.775	0.837		
	4 <sup>th</sup>	1.108	1.189		
	5 <sup>th</sup>	1.468	1.484		
	6 <sup>th</sup>	1.862	1.806		
	Reverse	3.333			
Differential gear ratio	1	0.239	0.258		
PERFORMANCE					
Max. speed (mph)		102	115		
0-62mph acceleration	(sec)	11.5	9.8		
FUEL CONSUMPTION, EMISSIONS,		1.5 100	1.5 130		
SERVICING. INSURA	NCE				
Combined cycle fuel	Active	47.55-51.36	-		
consumption WLTP,	Icon	47.55-51.36 SWB	-		
mpg)		42.9-51.36 LWB			
	Design	-	47.12-50.44		
Combined cycle CO <sub>2</sub>	Active	144-155.7	-		
emissions (WLTP,	Icon	144-155.65 SWB	-		
g/km)		145-171.37 LWB			
	Design	-	146-157.08		
Service intervals		25,000 miles/2 years			
Insurance groups		32E – 37E			
Fuel tank capacity (I)		50 + 17 fo	50 + 17 for AdBlue		

BRAKES			
Front	Ventilated discs		
Rear	Discs		
STEERING	SWB	LWB	
Туре	Speed-sensitive electric power-assisted		
Turning circle – tyre (m)	10.79	11.43	
Turning circle – body (m)	11.29	11.93	
SUSPENSION	SWB	LWB	
Front	MacPherson struts, anti-roll bar		
Rear	Torsion beam		
EXTERIOR DIMENSIONS	SWB	LWB	
Overall length (mm)	4,403	4,753	
Overall width – exc. mirrors (mm)	1,848		
Overall width – mirrors folded (mm)	2,	107	
Overall height (mm)	1,880		
Wheelbase (mm)	2,785	2,975	
Front track (mm)	1,548		
Rear track (mm)	1,568		
Front overhang (mm)	892		
Rear overhang (mm)	726		
Ground clearance (mm)	160		
LOAD COMPARTMENT (INTERIOR)	SWB	LWB	
DIMENSIONS			
Load floor length (mm)	1,817	2,167	
Load floor length with Smart Cargo (mm)	3,090	3,440	
Max. load height (mm)	1,200		
Max. load width – between sides (mm)	1,527		
Max. load width – between wheel arches	1,229		
(mm)			
Sliding side door max. opening height (mm)	1,072		
Sliding side door max. opening width (mm)	675		
Rear doors max. opening height (mm)	1,196		
Rear doors max. opening width – upper	1,087		
section (mm)			

Rear doors max. opening width – lower	1,241		
section (mm)			
Load area volume (m³)	3.3	3.9	
Load area volume with Smart Cargo (m³)	3.8	4.4	

WEIGHTS	Active	Icon	Design
Gross vehicle weight (kg)	2,390	2,390 2,400*	2,380
Min. kerb weight (kg)	1,404	1,404 1,426*	1,404
Max. kerb weight (kg)	1,627	1,702 1,693*	1,627
Towing capacity – unbraked (kg)	720	730 740*	730
Towing capacity – braked (kg)	1,200	1,200	1,200
Payload (kg)	1,000	1,000	1,000

<sup>\*</sup> Values for long wheelbase model

These specifications are provided as a guide for media only. Customers wishing to confirm the specification of a specific vehicle should check details with their Toyota centre or visit www.toyota.co.uk.