

TOYOTA PROACE ELECTRIC TECHNICAL SPECIFICATIONS

| DRIVETRAIN | | | |
|----------------------------------|----------------------------|---|-----|
| Electric motor | | | |
| Type | | Permanent magnet, synchronous motor | |
| Max. voltage | | 300 (50kWh battery) 450 (75kWh battery) | |
| Max. power (bhp/DIN hp/Kw) | Power | 134/136/100 | |
| | Normal | 108/110/80 | |
| | Eco | 81/82/60 | |
| Max. torque (Nm) | Power | 260 | |
| | Normal | 210 | |
| | Eco | 190 | |
| Battery | | | |
| Type | | Lithium-ion | |
| Nominal voltage | | 394 | |
| Total capacity (kWh) | | 50 | 75 |
| Number of modules | | 18 | 27 |
| Weight (kg) | | 383 | 534 |
| Battery charging | | | |
| Charging time | 230V | 7.5hr | |
| | Quick charge | 32min | |
| Connector type | AC input (normal use) | Type 2 | |
| | DC input (quick charge) | CHAdeMO | |
| Maximum AC charge rate (kWh) | | 11 | |
| TRANSMISSION | | | |
| Type | | Automatic | |
| Driven wheels | | Front | |
| Differential gear ratio | | 0.366 | |
| PERFORMANCE | | | |
| 0-62mph (sec)* | | 12.1 (50kW battery, power mode) 13.3 (75 kW battery, power mode) | |
| Max. speed (mph)* | | 80 (electronically limited) | |
| Driving range (miles, WLTP) | | 205 (75kWh battery) 142 (50kWh battery) | |
| INSURANCE | | | |
| Insurance group | | 40-41E | |
| BRAKES | | | |
| Front type/diameter (mm) | | Ventilated discs/304 | |
| Rear | | Solid discs/294 | |
| STEERING | | | |
| Type | | Rack and pinion | |
| Turning circle | Tyre (m) | 6.2 | |
| | Body (m) | 6.45 | |
| SUSPENSION | | | |
| Front | | MacPherson strut-type with coil springs and anti-roll bar | |
| Rear | | Trailing arms with coil springs and anti-roll bars | |

| EXTERIOR DIMENSIONS | | |
|---|----------------------|----------------------|
| Overall length (mm) | 4,959 | |
| Overall width (mm) | 1,920 | |
| Overall height (mm) | 1,890 | |
| Wheelbase (mm) | 3,275 | |
| Front track (mm) | 1,627 | |
| Rear track (mm) | 1,600 | |
| Front overhang (mm) | 881 | |
| Rear overhang (mm) | 803 | |
| LOAD AREA DIMENSIONS | | |
| Floor load length (mm) | 2,512 | |
| Floor load length with Smart Cargo (mm) | 3,674 | |
| Mid-height load length (mm) | 2,185 | |
| Max. load height (mm) | 1,397 | |
| Max. load width between sides (mm) | 1,628 | |
| Max. load width between wheel arches (mm) | 1,258 | |
| Sliding side door max. opening height (mm) | 1,241 | |
| Sliding side door max. opening width (mm) | 935 | |
| Rear door height (mm) | 1,220 | |
| Rear door width (mm) | 1,282 | |
| Load area volume (m ³) | 5.3 | |
| Load area volume with Smart Cargo (m ³) | 5.8 | |
| WEIGHTS | 50kWh battery | 75kWh battery |
| Gross vehicle weight (kg) | 3,100 | 3,025 |
| Kerb weight min-max (kg) | 1,874-2,050 | 2,025-2,201 |
| Max. payload (kg) | 1,226 | 1,000 |
| Towing capacity – braked (kg) | 1,000 | 1,000 |

These specifications are provided as a guide for media only. Customers wishing to confirm the specifications of a specific vehicle should confirm details with their Toyota centre or visit www.toyota.co.uk.