

TECHNICAL SPECIFICATIONS

Data remain provisional pending homologation

ENGINE		
Engine type		Four cylinders in-line
Displacement (cc)		2,755
Valvetrain		16-valve DOHC
Fuel injection type		Common rail
Bore x stroke (mm)		92.0 x 103.6
Max power (bhp/DIN hp/kW @ rpm)		201/204/150 @ 3,000 – 3,400
Max torque (Nm/rpm)		500 @ 1,600 – 2,800
TRANSMISSION		
Type		8AT
Ratios	1 st	4.413
	2 nd	2.808
	3 rd	1.950
	4 th	1.511
	5 th	1.274
	6 th	0.100
	7 th	0.793
	8 th	0.651
Reverse		3.645
Final drive ratio		3.583
PERFORMANCE		
Acceleration 0-62mph (sec)		Pending homologation
Max. speed (mph)		102 – 18in wheels 105 – 20in wheels
FUEL CONSUMPTION (WLTP)		
Combined cycle (mpg)		Pending homologation
Fuel tank capacity (l)		80
EMISSIONS (WLTP)		
Emissions standard		EURO6E
CO ₂ emissions (g/km)		Pending homologation
SUSPENSION		
Front		Double wishbone
Rear		Four-link rigid with lateral control arm
BRAKES		
Front		Ventilated discs
Rear		Ventilated discs
STEERING		
Type		Rack and pinion, electric power steering
Turns lock-to-lock		3.24
OFF-ROAD PERFORMANCE		
Approach angle (deg)		32

Departure angle (deg)	17
Minimum running ground clearance (mm)	215.3
DIMENSIONS	
Overall length (mm)	4,925
Overall width (mm)	1,980
Overall height (mm)	1,935
Wheelbase (mm)	2,850
Front track (mm)	1,664
Rear track (mm)	1,668
Front overhang (mm)	935
Rear overhang (mm)	1,140
Turning radius – tyre (m)	6.0
Turning radius – body (m)	6.4
Load space capacity (m ³ VDA)	1,063
WEIGHTS	
Kerb weight (kg)	2,330 – 2,550
Gross vehicle weight (kg)	3,150
Towing capacity – braked (kg)	3,500

ENDS