TOYOTA YARIS CROSS TECHNICAL SPECIFICATIONS

POWERTRAIN	1.5-litre Hybrid		
	114bhp	129bhp	
Туре	3 cylinders in-line		
Valve mechanism	DOHC 12-valve with VVT-iE (intake) and		
	VVT-i (exhaust)		
Fuel system	Direct multipoint injection		
Displacement (cc)	1,490		
Bore x stroke (mm)	80.5 x 97.6		
Compression ratio	14.0:1		
Max. torque (Nm @ rpm)	120 @ 3,600		
Max. engine power (bhp/DIN Hp/kW @ rpm)	90/91/68 @ 5,500		
Total hybrid system max. power (bhp/DIN	114/116/85	129/130/96	
hp/kW)			
Electric motor/generator (MG2)	114bhp	129bhp	
Motor type	Permanent magnet, synchronous motor		
Max. voltage (v)	580		
Max. power (kW)	59	62	
Max. torque (Nm)	141	185	
Rear electric motor (AWD-i)			
Motor type	Induction motor		
Max. power (kW)	3.9		
Max. torque (Nm)	52		
High-voltage battery			
Battery type	Lithium-ion		
Number of cells	48		
Nominal voltage (v)	177.6		
Capacity (amp/h)	4.3		
TRANSMISSION			
Туре	e-CVT		
Front gear ratio	3.218:1		
Rear gear ratio (AWD-i)	10.487		
PERFORMANCE	114bhp	129bhp	
Max. speed (mph)	10	09	
FWD	11.2	10.7	

0-62mph accelerati	on		
(sec)	AWD	11.8	11.3
FUEL CONSUMPTION (WLTP)		114bhp	129bhp
Combined cycle (mpg)		54.6-62.7	56.8-58.8
Fuel tank capacity (I)		36	
CO ₂ EMISSIONS (WLTP), INSURANCE,		114bhp	129bhp
WARRANTY & SE	RVICING		
Combined cycle (g/km)	Icon	101	-
	Design	103	-
	Excel FWD	112	-
	Excel AWD-i	115	-
	GR Sport	-	109
	Premiere Edition	-	109
	FWD		
	Premiere Edition	-	115
	AWD-i		
Insurance groups	-	11E – 14E	
New vehicle warranty		3 years/60,000 miles	
Service schedule		10,000 miles/annually	
BRAKES			
Front		Ventilated discs	
Rear		Solid discs	
Parking brake		Electronic	
SUSPENSION			
Front		MacPherson struts	
Rear		Torsion beam	
STEERING			
Туре		Rack and pinion, electric power	
		assistance	
Turns lock-to-lock		2.65	
Min. turning radius – body (m)		5.6	
Min. turning radius – tyre (m)		5.3	
EXTERIOR DIMEN	SIONS		
Overall length (mm)		4,172	
Overall width (mm)		1,765	

Overall height (mm)		1,595	
Wheelbase (mm)		2,560	
Front overhang (mm)		845	
Rear overhang (mm)		767	
Front track (mm)		1,520	
Rear track (mm)		1,519	
Coefficient of drag (Cd)		0.35	
INTERIOR DIMENSIO	NS		
Interior length (mm)		1,840	
Interior width (mm)		1,430	
Interior height (mm)		1,205	
Load capacity VDA	Seats up, loaded to	350	
(I)	tonneau cover (I)		
	Seats up, loaded to	460	
	roof (I)	1.097	
	Seats folded, loaded		
	to roof		
WEIGHTS		114bhp	129bhp
Kerb weight (kg)	FWD	1,190 - 1,275	1,230 – 1,260
	AWD-i	1,310 -1,345	1,320 – 1,355
Gross vehicle weight	FWD	1,690	1,690
(kg)	AWD-i	1,775	1,775
Towing capacity – braked (kg)		750	
Towing capacity – unbraked (kg)		550	
WHEELS & TYRES			
Wheels		16, 17 or 18in alloy	
Tyres	16in wheel	195/55R16	
	17in wheel	205/45R17	
	18in wheel	215/40R18	

These specifications are a guide for media only. Customers wishing to check the specification of a specific vehicle should contact their local Toyota centre or visit www.toyota.co.uk.