## **RAV4 TECHNICAL SPECIFICATIONS**

ENGINE				
Engine code		A25A	A25A-FXS	
Engine type		4 cylinders in-line		
Valve mechanism		16-valve DOHC, VVT-i (intake) and VVT-i		
		(exhaust)		
Fuel injection		D4S		
Displacement (cc)		2,487		
Bore x stroke (mm)		87.5 x 103.48		
Compression ratio		14.0:1		
Total system output (bhp/DIN hp/kW)		215/218/160 FWD		
		219/222/163 AWD-i		
Max. engine power (bhp/DIN hp/kW @ rpm)		176/178/131 @ 5,700		
Max. engine torque (Nm @ rpm)		221 @ 3,600 – 5,200		
Emissions certification		Euro 6d		
HYBRID SYSTEM				
Electric motor (front)				
Туре		AC permanent magnet, synchronous motor		
Max. power (kW)		88		
Max. torque (Nm)		202		
Electric motor (rear)				
Туре		AC permanent magnet, synchronous motor		
Max. power (kW)		40		
Max. torque (Nm)		121		
Hybrid battery				
Туре		Nickel-metal hydride		
Nominal voltage		244.8		
Number of modules		34		
System voltage		650		
TRANSMISSION		21	·~	
Type		CVT		
Final drive ratio		3.605:1		
PERFORMANCE		<b>FWD AWD-i</b> 112		
Max. speed (mph)				
0-62mph (sec)		8.4	8.1	
FUEL CONSUMPTION, EMISSIONS &		FWD	AWD-i	
INSURANCE Combined fuel	Design	48.7-49.5	47.0-48.7	
consumption – WLTP				
data (mpg)	Excel	48.7-49.5	47.0-48.7	
	GR Sport	n/a	47.0-48.7	
Fuel tank capacity (I)  CO <sub>2</sub> emissions – Design		55		
combined, WLTP data	Design Excel	129-132 130-132	131-137 131-137	
(g/km)	GR Sport		131-137	
	GN SPUIL	n/a 132-137 25E-32A		
Insurance groups  New vehicle warranty		3 years/60,000 miles		
SUSPENSION		3 years/60	5 years/00,000 miles	
303F LINSION				

Front		MacPherson strut	
Rear		Double wishbone	
Anti-roll bar diameter	Front	25.4	
(mm)	Rear	23	3.2
BRAKES			
Front (diameter, mm)		Ventilated discs, 328	
Rear (diameter, mm)		Solid discs, 317	
STEERING			
Туре		Rack and pinion, electric power steering	
Ratio		14.3:1	
Turns lock to lock		2.76	
Min. turning radius – tyre/body (m)		5.5/5.9	
TYRES AND WHEELS			
Wheel size		18 or 19-inch	
Tyre size		225/60R18	
		235/55R19	
WEIGHTS		FWD	AWD-i
Kerb weight (min/max kg)		1,590 – 1,680 1,650 – 1,730	
Towing capacity - unbraked (kg)		750	
Towing capacity - braked (kg)		800	1,650
Gross Vehicle Weight (k	C,	2,135	2,225
DIMENSIONS - EXTER	IOR		
Overall length (mm)		4,600	
Overall width (mm)		1,855	
Overall height (mm)		1,685	
Wheelbase (mm)		2,690	
Front track (mm)		1,610	
Rear track (mm)		1,640	
Front overhang (mm)		910	
Rear overhang (mm)		1,000	
Ground clearance (mm)		195	
Angle of approach (deg)		17.5	
Angle of departure (deg)		20	
Coefficient of drag (Cd)		0.32	
DIMENSIONS - INTERI	OR		
Interior length (mm)		1,890	
Interior width (mm)		1,515	
Interior height (mm)		1,230	
DIMENSIONS - LUGGA			
Capacity – rear seats in place (I)		580	
Capacity – rear seats folded, up to tonneau cover (I)		1,189	
Capacity – rear seats folded, up to roof (I)		1,690	
Load area height (mm)		1,015	

These specifications are intended as a guide for media. Customers requiring specification details of specific models should confirm these with their Toyota Centre or visit <a href="https://www.toyota.co.uk">www.toyota.co.uk</a>.