

TOYOTA PROACE VERSO EV TECHNICAL SPECIFICATIONS

POWERTRAIN		BEV	
Electric motor			
Type		Permanent magnet, synchronous motor	
Max. power (bhp/DIN hp/kW)		134/136/100	
Max. torque (Nm)		260	
Transmission		Automatic	
Battery			
Type		Lithium-ion	
Total capacity (kWh)		50	75
Weight (kg)		350	534
Battery charging		50kWh	75kWh
Charging time	DC rapid (0-80% approx.)	30min	45min
	AC wallbox (0-100% approx.)	7hr 10min	10hr 45min
	AC domestic (0-100% approx.)	21hr 45min	32hr 40min
PERFORMANCE			
Max. speed (mph)		80	
0-62mph (sec)		10.8 (50kWh) 11.9 (75kWh)	
Insurance groups		18-19E	
BRAKES			
Front		Ventilated discs	
Rear		Solid discs	
STEERING		MEDIUM	LONG
Type		Electro-hydraulic, rack and pinion	
Turning circle (m)	Tyre	12.4	12.4
	Body	12.9	12.9
SUSPENSION			
Front		MacPherson strut-type	
Rear		Wishbones with trailing arms, variable stiffness springs and load-adaptive shock absorbers	
EXTERIOR DIMENSIONS		MEDIUM	LONG
Overall length (mm)		4,981	5,331
Overall width (mm)		1,920	
Overall height (mm)		1,895	1,940
Wheelbase (mm)		3,275	
Front track (mm)		1,630	
Rear track (mm)		1,618	
Front overhang (mm)		901	901
Rear overhang (mm)		803	1,152
INTERIOR DIMENSIONS		MEDIUM	LONG
Interior length (mm)		3,161	3,511
Interior width (mm)		1,515	
Load area volume – loaded to tonneau cover (l)		550	980
Load area volume – loaded		700	1,300

to tonneau roof (l)		
WEIGHTS	MEDIUM	LONG
Gross vehicle weight (kg)	3,100	3,130
Kerb weight (kg)	2,136 – 2,457	2,166 – 2,421
Max. towing capacity – braked (kg)	1,000	
Max. towing capacity – unbraked (kg)	750	
WHEELS & TYRES		
Wheel type and size	16in steel or 17in alloy	
Tyre size	215/65R16 or 215/60R17	