RAV4 PLUG-IN TECHNICAL SPECIFICATIONS

2.5-litre HYBRID ENGINE	
Engine code	A25A-FXS
Engine type	4 cylinders in-line
Valve mechanism	16-valve DOHC, VVT-i (intake) and VVT-i
	(exhaust)
Fuel injection	D4S electronic fuel injection
Displacement (cc)	2,487
Bore x stroke (mm)	87.5 x 103.48
Compression ratio	14.0 <u>1</u> :1
Total system output (bhp/DIN hp/kW)	302/306/225
Max. engine power (bhp/kW @ rpm)	182/185/136 @ 6,000
Max. engine torque (Nm @ rpm)	227 @ 3,200 – 3,700
PLUG-IN HYBRID SYSTEM	
Electric motor (front)	
Туре	AC permanent magnet, synchronous motor
Max. power (kW)	134
Max. torque (Nm)	270
Electric motor (rear)	
Туре	AC permanent magnet, synchronous motor
Max. power (kW)	40
Max. torque (Nm)	121
Hybrid battery	
Туре	Lithium-ion
Nominal voltage	355.2
Number of modules	96
Capacity (kWh)	18.1
On-board charger (kW)	6.6
TRANSMISSION	
Туре	Planetary gear system
	All-Wheel Drive- intelligent (AWD-i)
Front gear ratio	3.412:1
Rear gear ratio	10.781:1
PERFORMANCE	110
Max. speed (mph)	112
0-62mph (sec)	6.0
EV driving range (WLTP combined cycle)	46.47 miles
FUEL CONSUMPTION, EMISSIONS & INSURANCE	
Combined fuel consumption – weighted	282.5
combined WLTP data (mpg)	
Fuel tank capacity (I)	55
CO ₂ emissions – weighted combined, WLTP data (g/km)	22
Insurance groups	36E – 37E
	<u> </u>

SUSPENSION		
Front		MacPherson strut
Rear		Double wishbone
Anti-roll bar diameter	Front	25.4
(mm)	Rear	23.2
` ,	Real	23.2
BRAKES		Vantilated diseas 240
Front (diameter, mm)		Ventilated discs, 340
Rear (diameter, mm)		Ventilated discs, 317
STEERING		D 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
Type		Rack and pinion, electric power steering
Ratio		14.4:1
Turns lock to lock		2.65
Min. turning radius – tyre/body (m)		5.9/6.1
TYRES AND WHEELS		
Wheel size		18 or 19in
Tyre size		225/60R18
		235/55R19
WEIGHTS	,	
Kerb weight (min/max k		1,910-2,005
Towing capacity - unbra		750
Towing capacity - braked (kg)		1,500
Gross Vehicle Weight (k		2,510
DIMENSIONS - EXTER	RIOR	
Overall length (mm)		4,600
Overall width (mm)		1,855
Overall height – including roof rails (mm)		1,690
Wheelbase (mm)		2,690
Front track (mm)		1,600
Rear track (mm)		1,630
Front overhang (mm)		910
Rear overhang (mm)		1,000
Ground clearance (mm)		190
Angle of approach (deg)		17.5
Angle of departure (deg)		20
Coefficient of drag (Cd)		0.32
DIMENSIONS - INTER	IOR	
Interior length (mm)		1,890
Interior width (mm)		1,515
Interior height (mm)		1,230
DIMENSIONS - LUGGA	AGE COMPARTMENT	
Capacity – rear seats in place, loaded to tonneau		520
cover, including space beneath deck board (I)		
Capacity – rear seats folded, up to tonneau cover		1,168
(I)		.,. 55
Capacity – rear seats fo	olded, up to roof (I)	1,604
- apasing roan coate relace, up to room (i)		1,001