

TOYOTA PROACE CITY VERSO TECHNICAL SPECIFICATIONS

DRIVETRAIN			
Electric motor			
Type	Permanent magnet, synchronous motor		
Max. voltage	418		
Nominal voltage	220		
Max. power (bhp/DIN hp/Kw)	Power	134/136/100	
	Normal	108/110/80	
	Eco	81/82/60	
Max. torque (Nm)	Power	270	
	Normal	210	
	Eco	180	
Battery			
Type	Lithium-ion		
Total capacity (kWh)	50		
Number of cells	216		
Number of modules	18		
Weight (kg)	380		
Battery charging			
On-board charger (kW)	11		
Charging time	Domestic socket	30.5hr	
	Wallbox	4.5hr	
	Fast charge	30min	
Connector type	AC input (normal use)	Type 2	
	DC input (quick charge)	CCS2 (Combo02)	
Maximum AC charge rate (kWh)	11		
TRANSMISSION			
Type	Automatic		
Driven wheels	Front		
Differential gear ratio	0.279		
PERFORMANCE			
0-62mph (sec)	11.2		
Max. speed (mph)	84		
Driving range (miles, WLTP)	213		
ENERGY CONSUMPTION & INSURANCE			
Energy consumption kWh/mile	0.3		
Insurance groups	18-21E		
BRAKES			
Front	Ventilated discs		
Rear	Solid discs		
STEERING		L1	L2
Type	Electric power-assisted rack and pinion		
Turning circle	Tyre (m)	10.82	11.43
	Body (m)	11.31	11.92
SUSPENSION			

Front	MacPherson strut-type	
Rear	Torsion beam	
EXTERIOR DIMENSIONS	L1	L2
Overall length (mm)	4,401	4,751
Overall width (mm)	1,848	
Overall height (mm)	1,812	1,818
Wheelbase (mm)	2,785	2,975
Front track (mm)	1,553	
Rear track (mm)	1,567	
Front overhang (mm)	890	
Rear overhang (mm)	726	886
INTERIOR DIMENSIONS	L1	L2
Interior height (mm)	1,200	
Interior length (mm)	3,300	3,500
Interior width (mm)	1,465	
Number of seats	5	7
Rear doors opening width/height (mm)	1,241/1,196	
Load area volume – loaded to belt line, rear seats up (VDA, l)	597	806
Load area volume – loaded to roof, rear seats up (VDA, l)	983	1538
WEIGHTS	L1	L2
Gross vehicle weight (kg)	2,360	2,440
Kerb weight min-max (kg)	1,736-1,928	1,847-1,909
Towing capacity – unbraked (kg)	750	0
Towing capacity – braked (kg)	750	0
WHEELS & TYRES		
Wheels	16in steel	
Tyres	215/65R16	

ENDS