TOYOTA YARIS CROSS TECHNICAL SPECIFICATIONS

POWERTRAIN	1.5-litre Hybrid		
	114bhp	129bhp	
Туре	3 cylinders in-line		
Valve mechanism	DOHC 12-valve with VVT-iE (intake) and		
	VVT-i (exhaust)		
Fuel system	Direct multipoint injection		
Displacement (cc)	1,490		
Bore x stroke (mm)	80.5 x 97.6		
Compression ratio	14.0:1		
Max. torque (Nm @ rpm)	120 @ 3,600		
Max. engine power (bhp/DIN Hp/kW @ rpm)	90/91/68 @ 5,500		
Total hybrid system max. power (bhp/DIN	114/116/85	129/130/96	
hp/kW)			
Electric motor/generator (MG2)	114bhp	129bhp	
Motor type	Permanent magnet, synchronous motor		
Max. voltage (v)	580		
Max. power (kW)	59	62	
Max. torque (Nm)	141	185	
Rear electric motor (AWD-i)			
Motor type	Induction motor		
Max. power (kW)	3.9		
Max. torque (Nm)	52		
High-voltage battery			
Battery type	Lithium-ion		
Number of cells	48		
Nominal voltage (v)	177.6		
Capacity (amp/h)	4.3		
TRANSMISSION			
Туре	e-CVT		
Front gear ratio	3.218:1		
Rear gear ratio (AWD-i)	10.487		
PERFORMANCE	114bhp	129bhp	
Max. speed (mph)	10	09	
FWD	11.2	10.7	

0-62mph acceleration				
(sec)	AWD	11.8	11.3	
FUEL CONSUMPTION (WLTP)		114bhp	129bhp	
Combined cycle (mpg)		54.6-62.7	56.8-58.8	
Fuel tank capacity (I)		36	6	
CO ₂ EMISSIONS (WLTP), INSURANCE,		114bhp	129bhp	
WARRANTY & SERV	ICING			
Combined cycle	Icon	101	-	
(g/km)	Design	103	102	
	Excel FWD	-	109	
	Excel AWD-i	-	115	
	GR Sport	-	109	
Insurance groups	1	11E – 14E		
New vehicle warranty		3 years/60,000 miles		
Service schedule	Service schedule		10,000 miles/annually	
BRAKES				
Front		Ventilated discs		
Rear		Solid discs		
Parking brake	Parking brake		Electronic	
SUSPENSION				
Front		MacPherson struts		
Rear		Torsion beam		
STEERING				
Туре		Rack and pinion, electric power		
		assistance		
Turns lock-to-lock	Turns lock-to-lock		2.65	
Min. turning radius – b	ody (m)	5.6		
Min. turning radius – ty	Min. turning radius – tyre (m)		5.3	
EXTERIOR DIMENSION	ONS			
Overall length (mm)		4,172		
Overall width (mm)		1,765		
Overall height (mm)		1,595		
Wheelbase (mm)		2,560		
Front overhang (mm)		845		
Rear overhang (mm)		767		

"PROTECTED 関係者外秘

Front track (mm)		1,520		
Rear track (mm)		1,519		
Coefficient of drag (Cd)		0.35		
INTERIOR DIMENSIO	NS			
Interior length (mm)		1,840		
Interior width (mm)		1,430		
Interior height (mm)		1,205		
Load capacity VDA	Seats up, loaded to	350		
(I)	tonneau cover (I)			
	Seats up, loaded to	460		
	roof (I)	1.097		
	Seats folded, loaded			
	to roof			
WEIGHTS		114bhp	129bhp	
Kerb weight (kg)	FWD	1,190 - 1,275	1,230 – 1,260	
	AWD-i	1,310 -1,345	1,320 – 1,355	
Gross vehicle weight	FWD	1,690	1,690	
(kg)	AWD-i	1,775	1,775	
Towing capacity – braked (kg)		750		
Towing capacity – unb	Towing capacity – unbraked (kg)		550	
WHEELS & TYRES				
Wheels		16, 17 or 18in alloy		
Tyres	16in wheel	195/55R16		
	17in wheel	205/45R17		
	18in wheel	215/40R18		

These specifications are a guide for media only. Customers wishing to check the specification of a specific vehicle should contact their local Toyota centre or visit www.toyota.co.uk.