## TOYOTA YARIS CROSS TECHNICAL SPECIFICATIONS

POWERTRAIN	1.5-litre Hybrid	
	114bhp	129bhp
Туре	3 cylinders in-line	
Valve mechanism	DOHC 12-valve with VVT-iE (intake) and	
	VVT-i (exhaust)	
Fuel system	Direct multipoint injection	
Displacement (cc)	1,490	
Bore x stroke (mm)	80.5 x 97.6	
Compression ratio	14.0:1	
Max. torque (Nm @ rpm)	120 @ 3,600	
Max. engine power (bhp/DIN Hp/kW @ rpm)	90/91/68 @ 5,500	
Total hybrid system max. power (bhp/DIN	114/116/85	129/130/96
hp/kW)		
Electric motor/generator (MG2)	114bhp	129bhp
Motor type	Permanent magnet, synchronous motor	
Max. voltage (v)	580	
Max. power (kW)	59	62
Max. torque (Nm)	141	185
Rear electric motor (AWD-i)		
Motor type	Induction motor	
Max. power (kW)	3.9	
Max. torque (Nm)	52	
High-voltage battery		
Battery type	Lithium-ion	
Number of cells	48	
Nominal voltage (v)	177.6	
Capacity (amp/h)	4.3	
TRANSMISSION		
Туре	e-CVT	
Front gear ratio	3.218:1	
Rear gear ratio (AWD-i)	10.487	
PERFORMANCE	114bhp	129bhp
Max. speed (mph)	10	09
FWD	11.2	10.7

0-62mph acceleration				
(sec)	AWD	11.8	11.3	
FUEL CONSUMPTION (WLTP)		114bhp	129bhp	
Combined cycle (mpg)		54.6-62.7	56.8-58.8	
Fuel tank capacity (I)		36	6	
CO <sub>2</sub> EMISSIONS (WLTP), INSURANCE,		114bhp	129bhp	
WARRANTY & SERV	ICING			
Combined cycle	Icon	101	-	
(g/km)	Design	103	102	
	Excel FWD	-	109	
	Excel AWD-i	-	115	
	GR Sport	-	109	
Insurance groups	Insurance groups		11E – 14E	
New vehicle warranty		3 years/60,000 miles		
Service schedule	Service schedule		10,000 miles/annually	
BRAKES				
Front		Ventilated discs		
Rear		Solid discs		
Parking brake		Electronic		
SUSPENSION				
Front		MacPherson struts		
Rear		Torsion beam		
STEERING				
Туре		Rack and pinion, electric power		
		assistance		
Turns lock-to-lock	Turns lock-to-lock		2.65	
Min. turning radius – b	ody (m)	5.6		
Min. turning radius – ty	Min. turning radius – tyre (m)		5.3	
EXTERIOR DIMENSION	ONS			
Overall length (mm)		4,172		
Overall width (mm)		1,765		
Overall height (mm)		1,595		
Wheelbase (mm)		2,560		
Front overhang (mm)		845		
Rear overhang (mm)		767		

## "PROTECTED 関係者外秘

Front track (mm)		1,520	
Rear track (mm)		1,519	
Coefficient of drag (Cd)		0.35	
INTERIOR DIMENSIO	NS		
Interior length (mm)		1,840	
Interior width (mm)		1,430	
Interior height (mm)		1,205	
Load capacity VDA	Seats up, loaded to	350	
(I)	tonneau cover (I)		
	Seats up, loaded to	460	
	roof (I)		
	Seats folded, loaded	1.097	
	to roof		
WEIGHTS		114bhp	129bhp
Kerb weight (kg)	FWD	1,190 - 1,275	1,230 – 1,260
	AWD-i	1,310 -1,345	1,320 – 1,355
Gross vehicle weight	FWD	1,690	1,690
(kg)	AWD-i	1,775	1,775
Towing capacity – braked (kg)		750	
Towing capacity – unbraked (kg)		550	
WHEELS & TYRES			
Wheels		16, 17 or 18in alloy	
Tyres	16in wheel	195/55R16	
	17in wheel	205/45R17	
	18in wheel	215/40R18	

These specifications are a guide for media only. Customers wishing to check the specification of a specific vehicle should contact their local Toyota centre or visit www.toyota.co.uk.