TOYOTA AYGO X HYBRID TECHNICAL SPECIFICATIONS

POWERTRAIN		
Туре	3 cylinders in-line	
Valve mechanism	DOHC 12-valve with VVT-iE (intake)	
	and VVT-i (exhaust)	
Fuel system	Direct multipoint injection	
Displacement (cc)	1,490	
Bore x stroke (mm)	80.5 x 97.6	
Compression ratio	14.0:1	
Max. torque (Nm @ rpm)	120 @ 3,600	
Max. engine power (bhp/DIN Hp/kW @	90/91/68 @ 5,500	
rpm)		
Total hybrid system max. power	114/116/85	
(bhp/DIN hp/kW)		
Electric motor/generator (MG2)		
Motor type	Permanent magnet, synchronous	
	motor	
Max. voltage (v)	580	
Max. power (kW)	59	
Max. torque (Nm)	141	
High-voltage battery		
Battery type	Lithium-ion	
Number of cells	48	
Nominal voltage (v)	177.6	
Capacity (amp/h)	4.3	
TRANSMISSION		
Туре	e-CVT	
Differential gear ratio	2.834	
PERFORMANCE		
Max. speed (mph)	107	
0-62mph acceleration (sec)	9.2	

FUEL CONSUMPTION (WLTP)	
Combined cycle (mpg)	72.4-74.3
Fuel tank capacity (I)	30
CO ₂ EMISSIONS (WLTP), INSURANCE,	
WARRANTY & SERVICING	
Combined cycle (WLTP, g/km)	87
Insurance groups	TBC
New vehicle warranty	3 years/60,000 miles
Service schedule	10,000 miles/annually
BRAKES	
Front	Ventilated discs
Rear	Solid discs
Parking brake	Electronic
SUSPENSION	
Front	MacPherson struts
Rear	Torsion beam
STEERING	
Туре	Rack and pinion, electric power
	assistance
Turns lock-to-lock	2.88
Min. turning radius – body (m)	5.0
Min. turning radius – tyre (m)	4.7
EXTERIOR DIMENSIONS	
Overall length (mm)	3,776
Overall width (mm)	1,740
Overall height (mm)	1,525
Wheelbase (mm)	2,430
Front overhang (mm)	806
Rear overhang (mm)	540
Front track (mm)	1,540
Rear track (mm)	1,520
Coefficient of drag (Cd)	0.31

"PROTECTED 関係者外秘

INTERIOR DIMENSIONS		
Interior length (mm)		1,700
Interior width (mm)		1,420
Interior height (mm)		1,205
Number of seats		4
Load capacity VDA (I)		231
WEIGHTS		
Kerb weight (kg)		1,095-1,175
Gross vehicle weight (kg)		1,510
Towing capacity – braked (kg)		n/a
Towing capacity – unbraked (kg)		n/a
WHEELS & TYRES		
Wheels		17 or 18in alloy
Tyres	17in wheel	TBC
	18in wheel	TBC