

GR YARIS TECHNICAL SPECIFICATIONS

ENGINE															
Code	G16E-GTS														
Type	3 cylinders in-line														
Valve mechanism	DOHC 12-valve with Dual VVT-i														
Fuel system	Direct & indirect, D-4ST														
Turbocharging	Single-scroll turbo with ball bearings														
Displacement (cc)	1,618														
Bore x stroke (mm)	87.5 x 89.7														
Compression ratio	10.5:1														
Max. power (bhp/DIN hp/kW @ rpm)	276/280/206 @ 6,500														
Max. torque (Nm @ rpm)	345 @ 3,150 – 4,600														
TRANSMISSION															
Type	6-speed iMT														
Ratios	<table> <tr> <td>1st</td><td>3.538</td></tr> <tr> <td>2nd</td><td>2.238</td></tr> <tr> <td>3rd</td><td>1.535</td></tr> <tr> <td>4th</td><td>1.162</td></tr> <tr> <td>5th</td><td>1.081</td></tr> <tr> <td>6th</td><td>0.902</td></tr> <tr> <td>Reverse</td><td>3.831</td></tr> </table>	1 st	3.538	2 nd	2.238	3 rd	1.535	4 th	1.162	5 th	1.081	6 th	0.902	Reverse	3.831
1 st	3.538														
2 nd	2.238														
3 rd	1.535														
4 th	1.162														
5 th	1.081														
6 th	0.902														
Reverse	3.831														
Differential gear ratio	3.941 (1 st to 4 th) 3.350 (5 th to 6 th & reverse)														
AWD system	GR-Four with electronically controlled multi-plate clutch														
Limited-slip differentials	Torsen, front and rear														
PERFORMANCE															
Max. speed (mph)	143														
0-62mph acceleration (sec)	5.2														
FUEL CONSUMPTION, EMISSIONS (WLTP) & INSURANCE															
Fuel consumption – combined cycle (mpg)	32.1 – 32.5														
Fuel tank capacity (l)	50														
CO ₂ emissions (g/km)	197														
Insurance groups	43A-44A														

SUSPENSION	
Front Suspension	MacPherson strut with reinforced lower arm
Rear suspension	Trailing double wishbones
STEERING	
Steering type	Rack and pinion electric power steering
Steering ratio	13.6:1
Turns lock-to-lock	2.36
Min. turning radius (m)	5.31 (tyre) 5.64 (body)
BRAKES	
Front, diameter x thickness (mm)	Two-piece ventilated, grooved discs, 356 x 28 with 4-pot aluminium monoblock callipers
Rear, diameter x thickness (mm)	Ventilated grooved discs 297 x 18 with 2-pot aluminium monoblock callipers
WHEELS & TYRES	
Wheels	18in BBS 8J forged aluminium
Tyres	225/40ZR18 Michelin Pilot Sport 4S
EXTERIOR DIMENSIONS	
Overall length (mm)	3,995
Overall width (mm)	1,805
Overall height (mm)	1,455
Wheelbase (mm)	2,560
Front track (mm)	1,535
Rear track (mm)	1,565
Running ground clearance (mm)	124
Coefficient of drag (Cd)	0.352
INTERIOR DIMENSIONS	
Length (mm)	1,785
Width (mm)	1,430
Height (mm)	1,175
Load space (VDA litres, rear seats in place)	174
WEIGHTS	
Kerb weight (min-max kg)	1,280-1,305
Gross vehicle weight (kg)	1,645

These specifications are a guide for media. Customers wishing to confirm the specification of a specific vehicle should consult their local Toyota centre or visit www.toyota.co.uk.