TOYOTA bZ4X TECHNICAL SPECIFICATIONS

DRIVETRAIN		**FWD**		**AWD**
		57.7kWh	**73.1kWh**	
Electric motors				
Type		Permanent magnet, synchronous motor		
Total power (bhp/DIN hp/kW)		166/167/123	221/224/165	338/343/252
Max. torque (Nm)		268.6		338.4
Battery		**57.7kWh**	**73.1kWh**	**73.1kWh**
Type		Lithium-ion		
Nominal voltage		288.6	384.8	
Capacity (kWh)		57.7	73.1	
Number of cells		78	104	
PERFORMANCE		**FWD 57.7kWh**	**FWD 73.1kWh**	**AWD 73.1kWh**
0-62mph (sec)		8.6	7.4	5.1
Max. speed (mph)		87	99	99
Driving range – WLTP (miles)	Icon	274	-	-
	Design	-	352	-
	Excel	-	319	292
Electric energy consumption (combined, miles/kWh)	18in wheels	4.47	4.47	4.29
	20in wheels	-	4.03	3.9
DIMENSIONS				
Overall length (mm)		4,690		
Overall width – excluding mirrors (mm)		1,860		
Overall height (mm)		1,650		
Wheelbase (mm)		2,850		
Track front (mm)		1,600		
Track rear (mm)		1,610		
Front overhang (mm)		915		
Rear overhang (mm)		925		
INTERIOR DIMENSIONS				
Interior length (mm)		1,918		
Interior width (mm)		1,502		
Interior height (mm)		1,149 (1,142 with Skyview roof)		
Load capacity (inc. under deckboard, VDA litres)		452		
WEIGHTS		**FWD 57.7kWh**	**FWD 73.1kWh**	**AWD 73.1kWh**
Kerb weight (kg)		1,850-1890	1,930-2,020	2,025-2,080
Gross vehicle weight (kg)		2,465	2,520	2,560
Towing capacity (kg)		750		
INSURANCE, SERVICING & WARRANTY				
Insurance group		TBC		
Service intervals		10,000 miles/annually		

Comprehensive new vehicle warranty		3 years/60,000 miles
Battery warranty		8 years/100,000 miles 10 years/650,000 miles with EV Care Battery Health Check
SUSPENSION		
Front		MacPherson strut
Rear		Trailing arms
BRAKES		
Front		Ventilated discs
Rear		Ventilated discs
Parking brake		Electronic
STEERING		
Type		Rack and pinion, electric power steering
Turns (lock to lock)		2.81
Min. turning radius (m)	Tyre	5.6
	Body	6.1
WHEELS & TYRES		
Wheel and tyre size		18in, 235/60R18 20in, 235/50R20
OFF-ROAD PEFORMANCE		
Angle of approach (deg)		17.4
Angle of departure (deg)		25.6
Min. running ground clearance (mm)		177 (with one passenger)
Wading depth (mm)		500